

City of Toronto's Climate Change Adaptation Strategy to Address Urban Flooding

Michael D'Andrea, M.E.Sc., P.Eng.
Chief Engineer and Executive Director
Engineering & Construction Services
City of Toronto

CERIU – INFRA 2017 Congress
December 4, 2017
Montreal, Canada

Presentation Overview

- City of Toronto Background
- Legislative and Policy Framework for Water Management in Toronto
- Climate Change Effects & Impacts From Recent Extreme Storms
- Adaptive Management Approach to Mitigating Urban Flooding
 - Watershed
 - Municipal
 - Private Property
- Policy Considerations and Conclusions

City of Toronto - Background

- **Canada's largest City:** 2.8 million
- **City of Toronto area:** 641 km²
 - Parkland (ravines, open space, etc.): 80 km²
- **Land Uses:**
 - 45% Residential
 - 23% Open space & natural areas
 - 10% Industrial
 - 9% Commercial
 - 13% Other
- **Rivers & Creeks:** 370 km
- **Elevation:**
 - 76.5 m at waterfront
 - 209 m at northern boundary
- **Lake Ontario Waterfront:** 43 km
- **Waterfront Beaches:** 11







City of Toronto – Funding Water Infrastructure

- Water and wastewater services in Toronto are rate-supported funding operating expenses and capital infrastructure improvements
 - NO reliance on property taxes
 - NO reliance on Provincial or Federal grants or funding
- Water Rate (2017): \$3.62/m³
- Average Annual Residential Annual Consumption: 265 m³
- Average Annual Residential Cost for Water: \$960
- Cost for all residential drinking water, wastewater and stormwater services: \$2.63 /day


Toronto's Water Infrastructure Assets

(Build-out History)



Toronto's Water Infrastructure Assets

- Combined Sewer Service Area




Legislative and Policy Framework

- **Legislation and regulations governing water are set by the Province of Ontario**
 - Provision of safe and reliable drinking water – applies to municipalities
 - Collection and treatment of wastewater – applies to municipalities
 - Management of stormwater – applies to municipalities AND “Conservation Authorities”
- **Provincial *Conservation Authorities Act*:**
 - First enacted in 1946 in response to concerns about poor land, water and forestry practices which were resulting in extensive soil loss and flooding
 - Governs watershed planning and enables the Province and municipalities to form “Conservation Authorities” within a specified watershed based geographic area to:
 - Manage watershed resources
 - Protect lives and property from riverine flooding and erosion



Legislative and Policy Framework

- Amendments to the Act (1956) as a result of the devastation caused by Hurricane Hazel (1954), where 81 lives lost
- Amendments empowered the Conservation Authorities to:
 - Prohibit filling of valley lands and flood plains
 - Implement proper land use planning, prohibiting urban development within flood-hazard areas such as floodplains
 - Construct flood protection works such as dams, reservoirs, flood control channels and erosion control works

Toronto & Region Conservation Authority – Flood Control Structures



Regional Flood Control





12 dams

Legislative and Policy Framework

- City of Toronto By-Laws and Standards:
 - Sewer and Watermain Design Criteria
 - Toronto Green Standard for New Urban Developments
 - Sewers (Sewage & Land Drainage) By-Law (Chapter 681 of the Municipal Code)
 - Mandatory Downspout Disconnection
 - Reverse Slope Driveway Prohibition
 - New Storm Sewer Connection Prohibition



Impacts from Extreme Storms

- Storm of August 19, 2005
 - Storm lasted 2 to 3 hours
 - Exceeded 1 in 100 year storm in northern part of City
 - Toronto's rain gauge station recorded 153 mm (6 inches)
 - Over 4,200 flooding complaints



Impacts from Extreme Storms

- Storm of July 8, 2013
 - Storm lasted 9 hours
 - Exceeded 1 in 100 year storm in western part of City
 - Toronto's rain gauge station recorded 138 mm (5.4 inches)
 - Over 4,700 flooding complaints




Impacts from Extreme Storms

- **Municipal Damage Summary**

- Damage to public infrastructure – roads, sewers and utilities
- Damage to streams, rivers and ravines – flash floods and bank erosion/collapse
- Impacts and threats to source water



Overland Flow Paths & Surface Flooding



Under extreme events & once sewer system is overloaded, ponding will occur, if there is no overland outlet

Impacts from Extreme Storms

- **Surface Flooding**


- Many low-points create ponding
- No outlet for extreme flooding
- Water backs onto private property
- Water enters basement:
 - Cracks in the basement walls
 - Doors
 - Window wells
 - Reverse-sloped driveways
- Poor lot grading
- Downspouts connected to sewer system



Impacts from Extreme Storms



General Observations

- Under “normal” storm conditions
 - Sewer systems perform as designed
- During extreme storms
 - Sanitary sewer system is overloaded
 - Widespread surface flooding (including private property)



Adaptive Management Approach to Mitigating Wet Weather Flow Impacts *(Water Quality and Urban Flooding)*

- **At the Municipal (City of Toronto) level**
 - Wet Weather Flow Master Plan (WWMFP)
 - Adopted by City Council in 2003
 - Watershed based approach
 - Uses a hierarchical approach to managing stormwater
 - Source Control (lot level)
 - Conveyance System (road allowance)
 - End-of-pipe (before discharge)
 - Public education a key component
 - 25-year implementation schedule



Adaptive Management Approach to Mitigating Urban Flooding


— *Basement Flooding Protection Program*

- **Adaptive Management Approach:**

- Approved by Council in April 2006
- Class Environmental Assessments required for storm drainage and sanitary sewer system improvements
- Upgrade Sewer Design Standards for Retrofit of Existing Systems:
 - Sanitary sewer back-up protection for May 2000 storm
 - Upgrade storm drainage systems to “New Development” standards: 100 year storm
- Lot Level Controls
- Sanitary Sewer System Improvements – as necessary
- Inlet Controls on Storm Sewer System
- Provide Overland Flow Control and/or Storage, as feasible
- Prioritization of Construction of System Improvements



Adaptive Management Approach to Mitigating Urban Flooding – Basement Flooding Protection Program



Source:
https://www1.toronto.ca/City%20of%20Toronto/Policy%2C%20Planning%2C%20Finance%20&%20Administration/Public%20Consultation%20Unit/Basement%20Flooding/Study%20Area%2041/small%20size%20BF_Study_Areas_Map_2017.jpg


Adaptive Management Approach to Mitigating Urban Flooding – Basement Flooding Protection Program

- **Surface Flow Controls**

- Catchbasin Inlet Control
- Increase number of Catchbasins
- Seal Maintenance Hole Covers
- Surface Flow Path Diversion


- **Involves:**

- Minimal effort and time to implement
- Will control excess stormwater from overloading the sewer system




Adaptive Management Approach to Mitigating Urban Flooding — *Basement Flooding Protection Program*

- **Pipe Conveyance Controls (Storm and Sanitary)**
 - Increasing Sewer Pipe Size
 - Relief Sewer (Twinning)
 - High Level Relief Storm Sewer
- **Involves:**
 - Road excavation within City limits
 - Removal of old sewer and structures
 - Disconnection of sewer service line
 - Placement of new sewer and structures
 - Reconnection of to new sewer
 - Restoration of road and boulevard



Adaptive Management Approach to Mitigating Urban Flooding – Basement Flooding Protection Program

- Storage for Sanitary and Storm




Offline and online underground storage tanks



Dry Pond

- Involves:

- Facilities constructed in existing parks or open spaces
- Temporary loss of open space and/or traffic disruptions
- Excavation and placement of storage elements
- Landscaping opportunities



Oversized Pipes (In-line storage)

Adaptive Management Approach to Mitigating Urban Flooding – *Basement Flooding Protection Program*

- **Lot Level Controls**

- Mandatory Downspout Disconnection (Phased in by 2013)
- Proper Lot Grading
- Installation of Backwater Valves on Sanitary Laterals
- Capping off of Storm Laterals & Installation of Sump Pump
- Repairing Cracks in Foundation Walls & Sealing Window Wells
- Covering Basement Stairwells
- Disconnecting “illegal” Sanitary Sewer Connections

- **PUBLIC EDUCATION !**



Adaptive Management Approach to Mitigating Urban Flooding — Basement Flooding Protection Program

- Public Education and Outreach

If you don't divert your downspout, your basement could flood.

Rainwater belongs on lawns and gardens where it can naturally filter into the ground. Not in downspouts which can overload the sewer system and cause basement flooding. Overloaded sewers can also send contaminated water into our lake and waterways. Please do the right thing and, if possible, divert your downspout onto your lawn or garden. For more information, go to toronto.ca/water/stopwater.

TORONTO



IS YOUR BASEMENT NEXT?

Together we can stop heavy rainfall, melting snow and runoff from ending up in your basement. At the City, we're doing our part by continuously updating and maintaining Toronto's complex underground pipes, sewers and catch basins. Now it's your turn. Find out how to flood-proof your home at toronto.ca/water.



BASEMENT FLOODS ARE ON THE RISE. DON'T LET YOUR BASEMENT BE NEXT.

Together we can stop heavy rainfall, melting snow and runoff from ending up in your basement. At the City, we're doing our part by continuously updating and maintaining Toronto's complex underground pipes, sewers and catch basins. Now it's your turn. Here are some tips to help you flood-proof your home.

<p>Fix cracks in your foundation.</p>	<p>Ensure the ground slopes away from your house.</p>
<p>Clear debris from eavestroughs and downspouts.</p>	<p>Install a sump pump to remove excess water.</p>
<p>Install a backwater valve to prevent water and sewage from backing up.</p>	<p>Divert your downspouts away from the foundation.</p>

For more information on flood-proofing your home, go to toronto.ca/water


TORONTO Call

Dry Pond - Muirhead Park


- Dry pond built in Muirhead Park in northern part of the City
- Completed in 2012 (\$2.3M)



During Construction – 2011



Courtesy: Google Maps




Dry Pond – Spring 2012




Old Sheppard Park – Stormwater Tank

- Located in North Toronto
- 12,000 m³ underground stormwater storage tank
- Completed in 2012 (\$10.2M)



Old Sheppard Park - Stormwater Tank



RECOMMENDED SOLUTIONS FOR CLUSTER 1 & 5



Investigation of Chronic Basement Flooding Sewershed Area 28

Figure 8.1: Recommended Solutions for Cluster 1 & 5

Drawn By: J.H. Checked By: A.F.
Date: Aug 12, 2008

Basement Flooding Protection Program

Cost Summary – (4 Study Areas Only: 14, 28, 29 & 30)

Improvement Work Category	Cost
<p>Sanitary Sewer Conveyance Controls (16 projects: replacement pipes, twinning, etc.)</p>	<p>\$ 6 M</p>
<p>Sanitary On-line/Off-line Storage Tanks (13 projects)</p>	<p>\$ 14 M</p>
<p>Storm Sewer Conveyance Controls (261 projects: replacement pipes, twinning, etc.)</p>	<p>\$163 M</p>
<p>Stormwater Storage Facilities (10 projects: underground storage tanks, dry ponds)</p>	<p>\$ 47 M</p>
<p>Lot Level & Surface Control Measures (downspout disconnection, add catchbasins, inlet controls, MH sealing, diversion etc.)</p>	<p>\$ 30 M</p>
<p>Basement Flooding Protection Subsidy</p>	<p>\$ 12 M</p>
<p>Total</p>	<p>\$272 M</p>

Adaptive Management Approach to Mitigating Urban Flooding — *Basement Flooding Protection Program*


- **Basement Flooding Protection Subsidy Program**

- Financial subsidy of up to \$3,200 per property, to install flood protection devices including:

- Backwater valve (max \$1,250)
- Sump pump (max \$1,750)
- Disconnection of a home's foundation drains (weeping tile) from the sewer system (max \$400)


- **Since the subsidy program was expanded City-wide (2006)**

- Over 19,500 applications have been approved
- More than \$32.4 million in total subsidy payments issued to property owners by Toronto Water as of the end of June 2016.
- On average, the City currently issues approximately \$1,600 in subsidy payments to participating properties.



Adaptive Management Approach to Mitigating Urban Flooding — *Basement Flooding Protection Program*

- Basement Flooding Protection Program Capital Plan:
 - \$1.53 Billion over the next 10 years



Residents' Appreciation



Policy Considerations and Conclusions

- Municipal infrastructure and corresponding service delivery is being impacted by more frequent extreme events
- Public/political expectations are very high
- Strong collaboration required among affected City departments and external agencies
- Joint responsibility: public must also assume some responsibility and affect change
- Funding considerations for system improvements:
 - Currently through water revenues
 - Future consideration for stormwater utility charge

Policy Considerations and Conclusions

- Standard design practices based on historical climate records
 - need to be reviewed based on projected new “norms”
- Advocate for “shared risk”:
 - Municipality, insurance industry...and property owner
- Establish design standard based on “acceptable risk”:
 - Ideally with insurance industry
- Need to consider acceptable or upset limit on expenditures:
 - e.g., cost per “benefiting property”

Policy Considerations and Conclusions

- Seize the opportunities to integrate adaptation:
 - New urban development:
 - Opportunity to do it right!
 - Lessons learned from older municipalities
 - Infrastructure renewal:
 - Opportunities to “shoe-horn” in adaptation
- From a social/economic standpoint:

*Assess the cost of adapting versus
the losses that can be expected if we don't!*

THANK YOU / MERCI

Michael D'Andrea, M.E.Sc., P.Eng.

Chief Engineer and Executive Director
Engineering & Construction Services
City of Toronto

E: michael.dandrea@toronto.ca

T: 416-392-8256